

# The noise clinic

Miguel Colom, Marc Lebrun, Jean-Michel Morel

CMLA, ENS Cachan

August 2012

## How to try it

A prototype of *noise clinic* is currently on line at  
[http://dev.ipol.im/~colom/ipol\\_demo/noise\\_clinic/](http://dev.ipol.im/~colom/ipol_demo/noise_clinic/)  
(username: demo, password: demo).

Other algorithms at Image Processing on Line <http://www.ipol.im/>:

*DCT-denoising*

*TV-denoising*

*K-SVD*

*NL-means*

*NL-Bayes*

Soon: *PLE*, *BLS-GSM*

# Outline I


- 1 Noise clinic: some good and bad patients
- 2 Multiscale signal-dependent noise model
- 3 Noise estimation methods for scale and signal dependent noise
- 4 Multiscale algorithm
- 5 Non local Bayesian denoising
- 6 Denoising recipes illustrated by DCT
- 7 References



# Denoised



# Difference



# Noise curves




Figure: Noise curves after denoising for image Bears, 3 first scales. ▶





# Difference



# Noise curves





Figure: Noise curves after denoising for image Frog, 3 first scales. ▶



Denoised



# Difference



# Noise curves








Figure: Noise curves after denoising for image Old Picture, 3 first scales.



# Denoised



# Difference



# Noise curves




Figure: Noise curves after denoising for image Marilyn 1, 3 first scales.


# Noisy



# Denoised



# Difference



# Noise curves





Figure: Noise curves after denoising for image Marilyn 2, 3 first scales.

An example of test image with wrong noise estimation





# Difference



# Noise curves




Figure: Noise curves after denoising for image Singer, 3 first scales. ▶



Figure: Comparison setting coefficient  $c = 1.0$ ,  $c = 3.0$ ,  $c = 4.0$ .



Figure: Comparison setting coefficient  $c = 1.0$ ,  $c = 3.0$ ,  $c = 4.0$ .



Figure: Comparison setting coefficient  $c = 1.0$ ,  $c = 3.0$ ,  $c = 4.0$ .

Noise clinic: some good and bad patients

**Multiscale signal-dependent noise model**

Noise estimation methods for scale and signal dependent noise

Multiscale algorithm

Non local Bayesian denoising

Denoising recipes illustrated by DCT

References

**Poisson noise**

Example of noise curve: raw image

Transforming signal-dependent noise into white Gaussian noise

Example: noise curve before/after the Anscombe transformation

Why multiscale noise evaluation?

Complete chain: from the raw to the final JPEG image

Noise model, and how it becomes complex from raw to JPEG

- Photon emission can be modelled with a random Poisson distribution due to the physical nature of light.

$$P(N = k) = \frac{e^{-\lambda t}(\lambda t)^k}{k!}$$

where  $k$  is the number of photons counted by the CCD,  $\lambda$  the expected number of photons/time unit.

- If  $N$  is large enough,  $N \sim \mathcal{N}(\lambda t, \lambda t)$ .

Noise clinic: some good and bad patients

Multiscale signal-dependent noise model

Noise estimation methods for scale and signal dependent noise

Multiscale algorithm

Non local Bayesian denoising

Denoising recipes illustrated by DCT

References

Poisson noise

Example of noise curve: raw image

Transforming signal-dependent noise into white Gaussian noise

Example: noise curve before/after the Anscombe transformation

Why multiscale noise evaluation?

Complete chain: from the raw to the final JPEG image




Figure: Left: Canon EOS 30D, ISO 1600,  $t=1/30s$  image. Right: noise curve of the raw image obtained with the Ponomarenko et al. algorithm.

- Most of the denoising algorithms only deal with uniform Gaussian noise.
- But raw images follow a Poisson distribution where the variance is proportional to the intensity.
- Solution: use a Variance Stabilizing Transformation:
- Anscombe transformation [1] ( $\Rightarrow \sigma^2 \approx 1$ ).

$$u \mapsto 2\sqrt{u + \frac{3}{8}}$$

(forward)

$$v \mapsto \left(\frac{v}{2}\right)^2 - \frac{3}{8}$$

(inverse)




Figure: Up: without and with the Anscombe transformation. Down: detailed view with the Anscombe transformation.








Figure: Typical JPEG noise curves at scales S0, S1, S2 and S3..



**Figure:** Effect of the complete IP pipeline for ISO 1600,  $t=1/30s$ , Canon EOS 30D: raw image, demosaicing, white balance, gamma correction and JPEG compression using photograph of a calibration pattern.

Noise clinic: some good and bad patients  
Multiscale signal-dependent noise model  
**Noise estimation methods for scale and signal dependent noise**  
Multiscale algorithm  
Non local Bayesian denoising  
Denoising recipes illustrated by DCT  
References

Noise estimation; slide on general principle (high frequency transform, use low qu  
Noise estimation algorithm #1: Ponomarenko et al  
Noise estimation algorithm #2: Percentile method  
Validation of the noise estimation methods with the GT  
Validation of the noise estimation methods with the GT  
Validation of the noise estimation methods with the GT  
Validation of the noise estimation methods with the GT

## Noise estimation methods

## General principles (for white noise first)

- Block-based methods.
- Get a estimation of the variance of data (noise+signal) inside each block using only the high frequencies of the block spectrum. The DCT<sup>1</sup> works quite well.
- Consider blocks whose variance is under a low quantile (typically 0.5%): keep only those blocks whose variance is explained mostly by the noise.
- Get the final estimation by combining the blocks in the low quantile. Typically, computing their median or using the MAD<sup>2</sup> estimator. Learn on noise the correction factor.

---

<sup>1</sup>Discrete Cosine Transform.

<sup>2</sup>Median of Absolute Deviations.

## Ponomarenko et al. noise estimation method

- Uses  $8 \times 8$  **overlapping blocks**.
- Sort the blocks by the variance of the **lower frequency** DCT coefficients of the block. Keep the lower (0.5%) quantile,
- The variance of the noise is estimated on the **medium and high frequency** coefficients of the blocks of this lower quantile.
- The **median** value of these variances gives the final variance estimation.

## Noise estimation algorithm #2: Percentile method

- The image is **high-passed** by convolving it with a **filter based on the DCT with support  $7 \times 7$**  to get rid of deterministic tendencies.
- Compute the variance of all  $21 \times 21$  **overlapping blocks**
- To discard those blocks whose variance is explained by the signal and not by the noise consider only the **small (0.5%) quantile**.
- The **median** of variances of this set gives the final variance estimation.

Noise clinic: some good and bad patients  
Multiscale signal-dependent noise model  
Noise estimation methods for scale and signal dependent noise  
Multiscale algorithm  
Non local Bayesian denoising  
Denoising recipes illustrated by DCT  
References

Noise estimation: slide on general principle (high frequency transform, use low q  
Noise estimation algorithm #1: Ponomarenko et al  
Noise estimation algorithm #2: Percentile method  
Validation of the noise estimation methods with the GT  
Validation of the noise estimation methods with the GT  
Validation of the noise estimation methods with the GT  
Validation of the noise estimation methods with the GT





Figure: Validation of the Ponomarenko et al. (left) and the Percentile methods (right) with a raw image with ISO 1250 and exposure time  $t=1/30s$ .








Figure: Validation of the Ponomarenko et al. (left) and the Percentile methods (right) with a raw image with ISO 1250 and exposure time  $t=1/400s$ .



**Figure:** Validation of the Ponomarenko et al. (left) and the Percentile methods (right) with a raw image with ISO 1600 and exposure time  $t=1/250s$ .







Figure: Validation of the Ponomarenko et al. (left) and the Percentile methods (right) with a raw image with ISO 1600 and exposure time  $t=1/640s$ .

## Multiscale denoising: principles

- signal dependent noise estimated at each scale
- zoom down followed by Anscombe transform to whiten the noise at each scale
- denoising performed at each scale, bottom-up (coarse to fine)
- Useful even for white noise: the denoising performance extends to very low frequencies





# More on the denoising algorithm: Non local Bayesian denoising

# Bayesian denoising in two slides

- patch noise model  $\mathbb{P}(\tilde{P}|P) = c \cdot e^{-\frac{\|\tilde{P}-P\|^2}{2\sigma^2}}$

# Bayesian denoising in two slides

- patch noise model  $\mathbb{P}(\tilde{P}|P) = c \cdot e^{-\frac{\|\tilde{P}-P\|^2}{2\sigma^2}}$
- Bayes' rule  $\mathbb{P}(P|\tilde{P}) = \frac{\mathbb{P}(\tilde{P}|P)\mathbb{P}(P)}{\mathbb{P}(\tilde{P})}$

# Bayesian denoising in two slides

- patch noise model  $\mathbb{P}(\tilde{P}|P) = c \cdot e^{-\frac{\|\tilde{P}-P\|^2}{2\sigma^2}}$
- Bayes' rule  $\mathbb{P}(P|\tilde{P}) = \frac{\mathbb{P}(\tilde{P}|P)\mathbb{P}(P)}{\mathbb{P}(\tilde{P})}$
- assume we got a patch Gaussian model  $\mathbb{P}(Q) = c \cdot e^{-\frac{(Q-\bar{P})^t \mathbf{C}_P^{-1} (Q-\bar{P})}{2}}$

# Bayesian denoising in two slides

- patch noise model  $\mathbb{P}(\tilde{P}|P) = c \cdot e^{-\frac{\|\tilde{P}-P\|^2}{2\sigma^2}}$
- Bayes' rule  $\mathbb{P}(P|\tilde{P}) = \frac{\mathbb{P}(\tilde{P}|P)\mathbb{P}(P)}{\mathbb{P}(\tilde{P})}$
- assume we got a patch Gaussian model  $\mathbb{P}(Q) = c \cdot e^{-\frac{(Q-\bar{P})^t \mathbf{C}_P^{-1} (Q-\bar{P})}{2}}$
- hence the variational problem

$$\begin{aligned} \max_P \mathbb{P}(P|\tilde{P}) &\Leftrightarrow \max_P \mathbb{P}(\tilde{P}|P)\mathbb{P}(P) \\ &\Leftrightarrow \max_P e^{-\frac{\|P-\tilde{P}\|^2}{2\sigma^2}} e^{-\frac{(P-\bar{P})^t \mathbf{C}_P^{-1} (P-\bar{P})}{2}} \\ &\Leftrightarrow \min_P \frac{\|P-\tilde{P}\|^2}{\sigma^2} + (P-\bar{P})^t \mathbf{C}_P^{-1} (P-\bar{P}). \end{aligned}$$

# Bayesian denoising in two slides

- patch noise model  $\mathbb{P}(\tilde{P}|P) = c \cdot e^{-\frac{\|\tilde{P}-P\|^2}{2\sigma^2}}$
- Bayes' rule  $\mathbb{P}(P|\tilde{P}) = \frac{\mathbb{P}(\tilde{P}|P)\mathbb{P}(P)}{\mathbb{P}(\tilde{P})}$
- assume we got a patch Gaussian model  $\mathbb{P}(Q) = c \cdot e^{-\frac{(Q-\bar{P})^t \mathbf{C}_P^{-1} (Q-\bar{P})}{2}}$
- hence the variational problem

$$\begin{aligned} \max_P \mathbb{P}(P|\tilde{P}) &\Leftrightarrow \max_P \mathbb{P}(\tilde{P}|P)\mathbb{P}(P) \\ &\Leftrightarrow \max_P e^{-\frac{\|P-\tilde{P}\|^2}{2\sigma^2}} e^{-\frac{(P-\bar{P})^t \mathbf{C}_P^{-1} (P-\bar{P})}{2}} \\ &\Leftrightarrow \min_P \frac{\|P-\tilde{P}\|^2}{\sigma^2} + (P-\bar{P})^t \mathbf{C}_P^{-1} (P-\bar{P}). \end{aligned}$$

- An empirical covariance matrix  $\mathbf{C}_{\tilde{P}}$  can be obtained for the patches  $\tilde{Q}$  similar to  $\tilde{P}$ .  $P$  and the noise  $n$  being independent,  
 $\mathbf{C}_{\tilde{P}} = \mathbf{C}_P + \sigma^2 \mathbf{I}; \quad E\tilde{Q} = \bar{P}$

# Bayesian denoising in two slides

$$\max_P \mathbb{P}(P|\tilde{P}) \Leftrightarrow \min_P \frac{\|P - \tilde{P}\|^2}{\sigma^2} + (P - \tilde{P})^t (\mathbf{C}_{\tilde{P}} - \sigma^2 \mathbf{I})^{-1} (P - \tilde{P})$$

# Bayesian denoising in two slides

$$\max_P \mathbb{P}(P|\tilde{P}) \Leftrightarrow \min_P \frac{\|P - \tilde{P}\|^2}{\sigma^2} + (P - \tilde{P})^t (\mathbf{C}_{\tilde{P}} - \sigma^2 \mathbf{I})^{-1} (P - \tilde{P})$$

one step estimation  $\hat{P}_1 = \tilde{P} + [\mathbf{C}_{\tilde{P}} - \sigma^2 \mathbf{I}]^{-1} \mathbf{C}_{\tilde{P}}^{-1} (\tilde{P} - \tilde{P})$ , where empirically:

$$\mathbf{C}_{\tilde{P}} \simeq \frac{1}{\#\mathcal{P}(\tilde{P}) - 1} \sum_{\tilde{Q} \in \mathcal{P}(\tilde{P})} (\tilde{Q} - \tilde{P})(\tilde{Q} - \tilde{P})^t, \quad \tilde{P} \simeq \frac{1}{\#\mathcal{P}(\tilde{P})} \sum_{\tilde{Q} \in \mathcal{P}(\tilde{P})} \tilde{Q}.$$

# Bayesian denoising in two slides

$$\max_P \mathbb{P}(P|\tilde{P}) \Leftrightarrow \min_P \frac{\|P - \tilde{P}\|^2}{\sigma^2} + (P - \tilde{P})^t (\mathbf{C}_{\tilde{P}} - \sigma^2 \mathbf{I})^{-1} (P - \tilde{P})$$

one step estimation  $\hat{P}_1 = \tilde{P} + [\mathbf{C}_{\tilde{P}} - \sigma^2 \mathbf{I}] \mathbf{C}_{\tilde{P}}^{-1} (\tilde{P} - \tilde{P})$ , where empirically:

$$\mathbf{C}_{\tilde{P}} \simeq \frac{1}{\#\mathcal{P}(\tilde{P}) - 1} \sum_{\tilde{Q} \in \mathcal{P}(\tilde{P})} (\tilde{Q} - \tilde{P})(\tilde{Q} - \tilde{P})^t, \quad \tilde{P} \simeq \frac{1}{\#\mathcal{P}(\tilde{P})} \sum_{\tilde{Q} \in \mathcal{P}(\tilde{P})} \tilde{Q}.$$

Iteration ("oracle estimation"):  $\hat{P}_2 = \tilde{P}^1 + \mathbf{C}_{\hat{P}_1} [\mathbf{C}_{\hat{P}_1} + \sigma^2 \mathbf{I}]^{-1} (\tilde{P} - \tilde{P}^1)$

where

$$\mathbf{C}_{\hat{P}_1} \simeq \frac{1}{\#\mathcal{P}(\hat{P}_1) - 1} \sum_{\hat{Q}_1 \in \mathcal{P}(\hat{P}_1)} (\hat{Q}_1 - \tilde{P}^1)(\hat{Q}_1 - \tilde{P}^1)^t, \quad \tilde{P}^1 \simeq \frac{1}{\#\mathcal{P}(\hat{P}_1)} \sum_{\hat{Q}_1 \in \mathcal{P}(\hat{P}_1)} \tilde{Q}.$$

# All Bayesian or Bayesian-like methods

Method	Denoising principle	Patches	size	Aggr.	Oracle	C
DCT	transform threshold	one	8	yes	yes	y
NL-Means	average	neighborhood	3	yes	yes	n
NL-Bayes	Bayes	neighborhood	3-7	yes	yes	y
PLOW	Bayes, 15 clusters	image	11	yes	yes	y
Shotgun	Bayes	$10^{10}$ patches	3-20	yes	no	n
EPLL	Bayes, 200 clusters	$2 \cdot 10^{10}$ patches	8	yes	yes	y
BLS-GSM	Bayes in GSM	Image	3	yes	no	n
K-SVD	sparse dictionary	Image	8	yes	yes	y
BM3D	transform threshold	neighborhood	8-12	yes	yes	y
PLE	Bayes, 19 clusters	Image	8	yes	yes	y

See: “Secrets of image denoising cuisine” M. Lebrun, M. Colom, A. Buades, J.M.M., *Acta Numerica*, 2012

# Conclusions in a nutshell:

- all methods except NL-means and Shotgun find an orthogonal or sparse basis for each patch.

# Conclusions in a nutshell:

- all methods except NL-means and Shotgun find an orthogonal or sparse basis for each patch.
- the final estimate is obtained by Wiener filter: applying optimal multiplicative coefficients to the coordinates of the patch on the basis

# Conclusions in a nutshell:

- all methods except NL-means and Shotgun find an orthogonal or sparse basis for each patch.
- the final estimate is obtained by Wiener filter: applying optimal multiplicative coefficients to the coordinates of the patch on the basis
- this is equivalent to Bayesian MMSE assuming that this basis gives a Gaussian model for the patch

# Conclusions in a nutshell:

- all methods except NL-means and Shotgun find an orthogonal or sparse basis for each patch.
- the final estimate is obtained by Wiener filter: applying optimal multiplicative coefficients to the coordinates of the patch on the basis
- this is equivalent to Bayesian MMSE assuming that this basis gives a Gaussian model for the patch
- coefficient thresholding (DCT) or averaging (NL-means) is suboptimal. By making them Bayesian, DCT thresholding becomes a DCT Wiener filter, and NL-means becomes NL-Bayes

# Conclusions in a nutshell:

- all methods except NL-means and Shotgun find an orthogonal or sparse basis for each patch.
- the final estimate is obtained by Wiener filter: applying optimal multiplicative coefficients to the coordinates of the patch on the basis
- this is equivalent to Bayesian MMSE assuming that this basis gives a Gaussian model for the patch
- coefficient thresholding (DCT) or averaging (NL-means) is suboptimal. By making them Bayesian, DCT thresholding becomes a DCT Wiener filter, and NL-means becomes NL-Bayes
- the mentioned methods differ only by the way the Gaussian mixture is constructed (global or local)

# Conclusions in a nutshell:

- all methods except NL-means and Shotgun find an orthogonal or sparse basis for each patch.
- the final estimate is obtained by Wiener filter: applying optimal multiplicative coefficients to the coordinates of the patch on the basis
- this is equivalent to Bayesian MMSE assuming that this basis gives a Gaussian model for the patch
- coefficient thresholding (DCT) or averaging (NL-means) is suboptimal. By making them Bayesian, DCT thresholding becomes a DCT Wiener filter, and NL-means becomes NL-Bayes
- the mentioned methods differ only by the way the Gaussian mixture is constructed (global or local)
- Shotgun is the ideal Bayesian MMSE algorithm. It makes no assumption at all (no Gaussianity)

# Conclusions in a nutshell:

- all methods except NL-means and Shotgun find an orthogonal or sparse basis for each patch.
- the final estimate is obtained by Wiener filter: applying optimal multiplicative coefficients to the coordinates of the patch on the basis
- this is equivalent to Bayesian MMSE assuming that this basis gives a Gaussian model for the patch
- coefficient thresholding (DCT) or averaging (NL-means) is suboptimal. By making them Bayesian, DCT thresholding becomes a DCT Wiener filter, and NL-means becomes NL-Bayes
- the mentioned methods differ only by the way the Gaussian mixture is constructed (global or local)
- Shotgun is the ideal Bayesian MMSE algorithm. It makes no assumption at all (no Gaussianity)
- All methods must be compared after applying the three denoising improvement tricks: color transform, aggregation, oracle iteration.

## All Bayesian or Bayesian-like methods, references

**DCT denoising:** G. Sapiro and G. Yu, IPOL 2011.

**NL-Bayes:** A. Buades, M. Lebrun, J.M.M., IPOL 2012.

**PLOW:** P. Chatterjee and P. Milanfar, TIP 2011.

**Shotgun:** A. Levin and B. Nadler, CVPR 2011.

**EPLL:** D. Zoran and Y. Weiss, ICCV 2011.

**BLS-GSM:** J. Portilla, V. Strela, M.J. Wainwright, and E.P. Simoncelli, TIP 2003.

**KSVD:** M. Elad, M. Aharon, TIP 2006.

**BM3D:** K. Dabov, A. Foi, V. Katkovnik, and K. Egiazarian, TIP 2007.

**PLE:** G. Yu, G. Sapiro, and S. Mallat, TIP 2010.

# Results of denoising a pure noise image ( $\sigma = 30$ ).

Method	PSNR	RMSE
NL-Bayes	45.45	1.36
BM3D	45.03	1.43
NL-means	41.45	2.16
TV denoising	41.06	2.26
DCT denoising	40.91	2.30
K-SVD	38.44	3.05

## PSNR table for $\sigma = 20, 30$ and $40$

	$\sigma = 20$				
NL-Bayes	BM3D	BLS-GSM	K-SVD	NL-means	DCT denoising
<b>33.45</b>	33.22	32.61	32.25	31.98	32.20

# PSNR table for $\sigma = 20, 30$ and $40$

		$\sigma = 20$			
NL-Bayes	BM3D	BLS-GSM	K-SVD	NL-means	DCT denoising
<b>33.45</b>	33.22	32.61	32.25	31.98	32.20
		$\sigma = 30$			
<b>31.37</b>	31.17	30.31	30.48	29.77	29.83

# PSNR table for $\sigma = 20, 30$ and $40$

	$\sigma = 20$				
NL-Bayes	BM3D	BLS-GSM	K-SVD	NL-means	DCT denoising
<b>33.45</b>	33.22	32.61	32.25	31.98	32.20
	$\sigma = 30$				
<b>31.37</b>	31.17	30.31	30.48	29.77	29.83
	$\sigma = 40$				
<b>30.15</b>	29.71	28.94	28.90	28.25	28.05



Figure: Original, noisy, DCT sliding window, BLS-GSM



Figure: Original, noisy, NL-means, K-SVD



Figure: Original, noisy, BM3D and Non-local Bayes.

## Ideal Bayesian method: Shotgun NL-means (A. Levin, B. Nadler 2011)

$$\mathbb{P}(\tilde{P} | P) = \frac{1}{(2\pi\sigma^2)^{\frac{\kappa^2}{2}}} e^{-\frac{\|P-\tilde{P}\|^2}{2\sigma^2}}, \quad (1)$$

## Ideal Bayesian method: Shotgun NL-means (A. Levin, B. Nadler 2011)

$$\mathbb{P}(\tilde{P} | P) = \frac{1}{(2\pi\sigma^2)^{\frac{\kappa^2}{2}}} e^{-\frac{\|P-\tilde{P}\|^2}{2\sigma^2}}, \quad (1)$$

Given a noisy patch  $\tilde{P}$  its optimal estimator for the Bayesian minimum squared error (MMSE) is by Bayes' formula

$$\hat{P} = \mathbb{E}[P | \tilde{P}] = \int \mathbb{P}(P | \tilde{P}) P dP = \int \frac{\mathbb{P}(\tilde{P} | P)}{\mathbb{P}(\tilde{P})} \mathbb{P}(P) P dP. \quad (2)$$

# Ideal Bayesian method: Shotgun NL-means (A. Levin, B. Nadler 2011)

$$\mathbb{P}(\tilde{P} | P) = \frac{1}{(2\pi\sigma^2)^{\frac{\kappa^2}{2}}} e^{-\frac{\|P - \tilde{P}\|^2}{2\sigma^2}}, \quad (1)$$

Given a noisy patch  $\tilde{P}$  its optimal estimator for the Bayesian minimum squared error (MMSE) is by Bayes' formula

$$\hat{P} = \mathbb{E}[P | \tilde{P}] = \int \mathbb{P}(P | \tilde{P}) P dP = \int \frac{\mathbb{P}(\tilde{P} | P)}{\mathbb{P}(\tilde{P})} \mathbb{P}(P) P dP. \quad (2)$$

Using a huge set of  $M$  natural patches,

$\mathbb{P}(P) dP \simeq \frac{1}{M}$  and  $\mathbb{P}(\tilde{P}) \simeq \frac{1}{M} \sum_i \mathbb{P}(\tilde{P} | P_i)$ . Thus

$$\hat{P} \simeq \frac{\frac{1}{M} \sum_i \mathbb{P}(\tilde{P} | P_i) P_i}{\frac{1}{M} \sum_i \mathbb{P}(\tilde{P} | P_i)}.$$

# Shotgun NL-means

- **Input:** Noisy image  $\tilde{u}$ , its patches  $\tilde{P}$

## Shotgun NL-means

- **Input:** Noisy image  $\tilde{u}$ , its patches  $\tilde{P}$
- **Input:** Very large set of  $M = 2^{10}$  patches  $P_i$  extracted from a large set of noiseless natural images (20000)

## Shotgun NL-means

- **Input:** Noisy image  $\tilde{u}$ , its patches  $\tilde{P}$
- **Input:** Very large set of  $M = 2^{10}$  patches  $P_i$  extracted from a large set of noiseless natural images (20000)
- **Output:** Denoised image  $\hat{u}$ .

# Shotgun NL-means

- **Input:** Noisy image  $\tilde{u}$ , its patches  $\tilde{P}$
- **Input:** Very large set of  $M = 2^{10}$  patches  $P_i$  extracted from a large set of noiseless natural images (20000)
- **Output:** Denoised image  $\hat{u}$ .
- **for all patches  $\tilde{P}$  extracted from  $\tilde{u}$ :** Compute the MMSE denoised estimate of  $\tilde{P}$

$$\hat{P} \simeq \frac{\sum_{i=1}^M \mathbb{P}(\tilde{P} | P_i) P_i}{\sum_{i=1}^M \mathbb{P}(\tilde{P} | P_i)}$$

where  $\mathbb{P}(\tilde{P} | P_i)$  is known from the Gaussian noise distribution.

# Shotgun NL-means

- **Input:** Noisy image  $\tilde{u}$ , its patches  $\tilde{P}$
- **Input:** Very large set of  $M = 2^{10}$  patches  $P_i$  extracted from a large set of noiseless natural images (20000)
- **Output:** Denoised image  $\hat{u}$ .
- **for all patches  $\tilde{P}$  extracted from  $\tilde{u}$ :** Compute the MMSE denoised estimate of  $\tilde{P}$

$$\hat{P} \simeq \frac{\sum_{i=1}^M \mathbb{P}(\tilde{P} | P_i) P_i}{\sum_{i=1}^M \mathbb{P}(\tilde{P} | P_i)}$$

where  $\mathbb{P}(\tilde{P} | P_i)$  is known from the Gaussian noise distribution.

- (Aggregation) : for each pixel  $\mathbf{j}$  of  $u$ , compute the denoised version  $\hat{u}_{\mathbf{j}}$  as the average of all values  $\hat{P}(\mathbf{j})$  for all patches containing  $\mathbf{j}$ .

Noise clinic: some good and bad patients

Multiscale signal-dependent noise model

Noise estimation methods for scale and signal dependent noise

Multiscale algorithm

Non local Bayesian denoising

**Denoising recipes illustrated by DCT**

References

# Denoising recipes illustrated by DCT

# Noise reduction, generic recipes

- Aggregation of estimates (of patches containing a given pixel)
- Iteration and oracle filters: use first step result as oracle for second step
- Color: convert  $(R, G, B)$  into  $(Y, U, V)$ .

# Tricks improving denoising performance



**Figure:** Original, noisy ( $\sigma = 25$ ), sliding DCT thresholding filter, incremental use of a  $Y_oU_oV_o$  colour system, uniform aggregation, variance based aggregation and iteration with the “oracle” given by the first step. Corresponding PSNRs : 26.85, 27.33, 30.65, 30.73, 31.25.

# Tricks improving denoising performance



**Figure:** Original, noisy ( $\sigma = 25$ ), sliding DCT thresholding filter, incremental use of a  $Y_oU_oV_o$  colour system, uniform aggregation, variance based aggregation and iteration with the “oracle” given by the first step. Corresponding PSNRs : 26.85, 27.33, 30.65, 30.73, 31.25.

# Tricks improving denoising performance



**Figure:** Original, noisy ( $\sigma = 25$ ), sliding DCT thresholding filter, incremental use of a  $Y_oU_oV_o$  colour system, uniform aggregation, variance based aggregation and iteration with the “oracle” given by the first step. Corresponding PSNRs : 26.85, 27.33, 30.65, 30.73, 31.25.

# Tricks improving denoising performance



**Figure:** Original, noisy ( $\sigma = 25$ ), sliding DCT thresholding filter, incremental use of a  $Y_oU_oV_o$  colour system, uniform aggregation, variance based aggregation and iteration with the “oracle” given by the first step. Corresponding PSNRs : 26.85, 27.33, 30.65, 30.73, 31.25.

# Tricks improving denoising performance



**Figure:** Original, noisy ( $\sigma = 25$ ), sliding DCT thresholding filter, incremental use of a  $Y_oU_oV_o$  colour system, uniform aggregation, variance based aggregation and iteration with the “oracle” given by the first step. Corresponding PSNRs : 26.85, 27.33, 30.65, 30.73, 31.25.

# Tricks improving denoising performance



**Figure:** Original, noisy ( $\sigma = 25$ ), sliding DCT thresholding filter, incremental use of a  $Y_oU_oV_o$  colour system, uniform aggregation, variance based aggregation and iteration with the “oracle” given by the first step.  
Corresponding PSNRs : 26.85, 27.33, 30.65, 30.73, 31.25.

# Tricks improving denoising performance



**Figure:** Original, noisy ( $\sigma = 25$ ), sliding DCT thresholding filter, incremental use of a  $Y_oU_oV_o$  colour system, uniform aggregation, variance based aggregation and iteration with the “oracle” given by the first step. Corresponding PSNRs : 26.85, 27.33, 30.65, 30.73, 31.25.

# Tricks improving denoising performance



**Figure:** Original, noisy ( $\sigma = 25$ ), sliding DCT thresholding filter, incremental use of a  $Y_oU_oV_o$  colour system, uniform aggregation, variance based aggregation and iteration with the “oracle” given by the first step. Corresponding PSNRs : 26.85, 27.33, 30.65, 30.73, 31.25.

# DCT denoising algorithm, step 1

Cancels DCT coefficients lower than  $3\sigma$ . Applied independently to each  $Y_o U_o V_o$  component.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation,  $\kappa = 8$ : size of patches,  $h = 3\sigma$ : threshold parameter.

# DCT denoising algorithm, step 1

Cancels DCT coefficients lower than  $3\sigma$ . Applied independently to each  $Y_o U_o V_o$  component.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation,  $\kappa = 8$ : size of patches,  $h = 3\sigma$ : threshold parameter.
- **For each noisy patch:**  $\tilde{P}$ : Compute the *DCT* transform of  $\tilde{P}$ .

# DCT denoising algorithm, step 1

Cancels DCT coefficients lower than  $3\sigma$ . Applied independently to each  $Y_o U_o V_o$  component.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation,  $\kappa = 8$ : size of patches,  $h = 3\sigma$ : threshold parameter.
- **For each noisy patch:**  $\tilde{P}$ : Compute the *DCT* transform of  $\tilde{P}$ .
- Cancel coefficients of  $\tilde{P}$  with magnitude lower than  $h = 3\sigma$ .

# DCT denoising algorithm, step 1

Cancels DCT coefficients lower than  $3\sigma$ . Applied independently to each  $Y_o U_o V_o$  component.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation,  $\kappa = 8$ : size of patches,  $h = 3\sigma$ : threshold parameter.
- **For each noisy patch:**  $\tilde{P}$ : Compute the *DCT* transform of  $\tilde{P}$ .
- Cancel coefficients of  $\tilde{P}$  with magnitude lower than  $h = 3\sigma$ .
- Compute the inverse DCT transform obtaining  $\hat{P}$ .

# DCT denoising algorithm, step 1

Cancels DCT coefficients lower than  $3\sigma$ . Applied independently to each  $Y_o U_o V_o$  component.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation,  $\kappa = 8$ : size of patches,  $h = 3\sigma$ : threshold parameter.
- **For each noisy patch:**  $\tilde{P}$ : Compute the *DCT* transform of  $\tilde{P}$ .
- Cancel coefficients of  $\tilde{P}$  with magnitude lower than  $h = 3\sigma$ .
- Compute the inverse DCT transform obtaining  $\hat{P}$ .
- Compute the aggregation weight  
 $w_{\tilde{P}} = 1/\#\{\text{number of non-zero DCT coefficients}\}$ .
- **for each pixel  $\mathbf{i}$ :** (aggregation) average all values at  $\mathbf{i}$  of all denoised patches  $\hat{Q}$  containing  $\mathbf{i}$ , weighted by  $w_{\tilde{Q}}$ .

## DCT denoising algorithm, step 2

A Wiener filter is applied in the “oracle” second step.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation, prefiltered image  $\hat{u}_1$  for “oracle” estimation.

## DCT denoising algorithm, step 2

A Wiener filter is applied in the “oracle” second step.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation, prefiltered image  $\hat{u}_1$  for “oracle” estimation.
- **For each pixel  $\mathbf{i}$ :**
- Take reference patches  $\tilde{P}$  and  $P_1$  around  $\mathbf{i}$  in  $\tilde{u}$  and  $\hat{u}_1$ .

## DCT denoising algorithm, step 2

A Wiener filter is applied in the “oracle” second step.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation, prefiltered image  $\hat{u}_1$  for “oracle” estimation.
- **For each pixel  $\mathbf{i}$ :**
- Take reference patches  $\tilde{P}$  and  $P_1$  around  $\mathbf{i}$  in  $\tilde{u}$  and  $\hat{u}_1$ .
- Compute the *DCT* transforms of  $\tilde{P}$  and  $P_1$ .

## DCT denoising algorithm, step 2

A Wiener filter is applied in the “oracle” second step.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation, prefiltered image  $\hat{u}_1$  for “oracle” estimation.
- **For each pixel  $\mathbf{i}$ :**
  - Take reference patches  $\tilde{P}$  and  $P_1$  around  $\mathbf{i}$  in  $\tilde{u}$  and  $\hat{u}_1$ .
  - Compute the *DCT* transforms of  $\tilde{P}$  and  $P_1$ .
  - Modify DCT coefficients of  $\tilde{P}$  as  $\tilde{P}(i) = \tilde{P}(i) \frac{P_1(i)^2}{P_1(i)^2 + \sigma^2}$ .

## DCT denoising algorithm, step 2

A Wiener filter is applied in the “oracle” second step.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation, prefiltered image  $\hat{u}_1$  for “oracle” estimation.
- **For each pixel  $\mathbf{i}$ :**
  - Take reference patches  $\tilde{P}$  and  $P_1$  around  $\mathbf{i}$  in  $\tilde{u}$  and  $\hat{u}_1$ .
  - Compute the *DCT* transforms of  $\tilde{P}$  and  $P_1$ .
  - Modify DCT coefficients of  $\tilde{P}$  as  $\tilde{P}(i) = \tilde{P}(i) \frac{P_1(i)^2}{P_1(i)^2 + \sigma^2}$ .
  - Compute the inverse DCT transform obtaining  $\hat{P}$ .

## DCT denoising algorithm, step 2

A Wiener filter is applied in the “oracle” second step.

- **Input:** noisy image  $\tilde{u}$ ,  $\sigma$  noise standard deviation, prefiltered image  $\hat{u}_1$  for “oracle” estimation.
- **For each pixel  $\mathbf{i}$ :**
  - Take reference patches  $\tilde{P}$  and  $P_1$  around  $\mathbf{i}$  in  $\tilde{u}$  and  $\hat{u}_1$ .
  - Compute the *DCT* transforms of  $\tilde{P}$  and  $P_1$ .
  - Modify DCT coefficients of  $\tilde{P}$  as  $\tilde{P}(i) = \tilde{P}(i) \frac{P_1(i)^2}{P_1(i)^2 + \sigma^2}$ .
  - Compute the inverse DCT transform obtaining  $\hat{P}$ .
  - Aggregation:  $w_{\tilde{P}} = 1/\#\{\text{number of non-zero DCT coefficients}\}$ ;
  - Average all values at  $\mathbf{i}$  of all denoised patches  $\hat{Q}$  containing  $\mathbf{i}$ , weighted by  $w_{\tilde{Q}}$ .



F. J. Anscombe.

The transformation of Poisson, binomial and negative-binomial data.  
*Biometrika*, 35(3):246–254, 1948.



P. Milanfar.

A tour of modern image filtering.  
*Invited feature article to IEEE Signal Processing Magazine (preprint at <http://users.soe.ucsc.edu/milanfar/publications/>)*, 2011.



N. N. Ponomarenko, V. V. Lukin, M. S. Zriakhov, A. Kaarna, and J. T. Astola.

An automatic approach to lossy compression of AVIRIS images.  
*IEEE International Geoscience and Remote Sensing Symposium*, 2007.